Hyperion® DA6 | Technical Data Sheet

Product Application

Due to its excellent surfactant properties the Hyperion® DA6 has numerous uses. It has an excellent wetting action especially in the low temperature range with degreasing and emulsifying properties. The main fields of application are: Cleaners for the textile industry, Metallurgy industry, paper industry.

Physical and Chemical Characteristics

Technical Data	Specs
Appearance	Clear, slightly cloudy liquid
pH (10% sol.)	4-7
Cloud point (1% sol.)	49.5

Storage

Hyperion® DA6 can be stored at least 2 years in original sealed container at room temperature under the recommended conditions. Protect from cold exposure during transport and storage. If the **Hyperion® DA6** becomes turbid, thick or freezes from cold exposure, unfreeze slowly at room temperature and then stir slowly.

Packaging

Hyperion® DA6 can be delivered in 205kg drums, or 1000 kg totes.



Novachem USA LLC

801 Brickell Avenue Suite 900 Miami, FL 33131

Novachem Asia

Room 2306, Block A Wanda Plaza, Weirqiao Huishan District, Wuxi City, China

Novachem S de RL

Zoli INHDELVA Nave 4B, INHDELVA NORTE Choloma, Cortes Honduras



Hyperion® is a registered brand of **Novachem**

URL:// www.novachemgroup.com

The above recommendations are based on extensive results done in the most professional manner. The user must try this product industrially first, to verify if the product is viable for further use. The technical information and application advice given in this **Novachem** publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. These results however verified and certified by a third party, do not hold us liable in terms of performance deviations. These tests have been conducted in controlled environments. The user is responsible for checking the suitability of products for their intended use.

For further information and to request samples, please visit **novachemgroup.com** where a qualified technician will assist you.

