

Ultralube® PED-35 | Technical Data Sheet

Product Information

Ultralube® PED-35 is a consistency-improving agent and additive to reduce fiber-to-fiber and metal-to-fiber tensile strength loss and abrasion resistance. Improves crease recovery and needle lubrication in sewing.

Benefits

- Compatible with N-methylol compounds
- Compatible with softeners/hydrophilic agents
- Improves sewing
- Prevents loop damage
- Retains color when gently washed
- Suitable for colored or white products
- Provides a smooth surface

Physical and Chemical Characteristics

Technical Data	Specs
Appearance	Beige liquid
pH	5-7
Density	0.95-1.20 g/ml
Solids (%)	31-34
Solubility	Easily soluble in water
Ionic character	Non ionic, slightly cationic in an acid environment.

Product Application

Ultralube® PED-35 is normally applied during the finishing stage on pads. Recommended doses depend on the purpose of use.

We recommend between 5.0 g/l - 15 g/l.

Storage

This product can be stored up to 12 months with no problem, we recommend not exceeding the temperature range between 4°C - 40°C while being stored. If product is held beyond its 12 month manufacturing date, please run stability test to guarantee stability of the product.

Packaging

Ultralube® PED-35 can be shipped in 200 kg drums and 1000 kg totes.

Novachem USA LLC

801 Brickell Avenue
Suite 900
Miami, FL 33131

Novachem Asia

Room 2306, Block A
Wanda Plaza, Weirjiao
Huishan District, Wuxi City, China

Novachem S de RL

Zoli INHDELVA
Nave 4B, INHDELVA NORTE
Choloma, Cortes
Honduras



Ultralube® is a registered brand
of **Novachem**

URL:// www.novachemgroup.com

The above recommendations are based on extensive results done in the most professional manner. The user must try this product industrially first, to verify if the product is viable for further use. The technical information and application advice given in this **Novachem** publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. These results however verified and certified by a third party, do not hold us liable in terms of performance deviations. These tests have been conducted in controlled environments. The user is responsible for checking the suitability of products for their intended use.

For further information and to request samples, please visit **novachemgroup.com** where a qualified technician will assist you.